

pro lite mdf

SENTRY DOOR-BLANKS

2012

- B** Approved Document B – Fire Resistance ✓
- E** Approved Document E – Acoustic Performance ✓
- L** Approved Document L – Thermal Performance ✓
- High Quality MDF faces (6mm)
- Lightweight / tri-layer solid timber core
- Comprehensive approvals for 30 minute fire resistance

Construction Specification:

The core of PRO LITE MDF comprises a tri-layer low density hardwood construction. The core is faced with 6mm MDF.

Size Adjustment:

Leaves may be reduced in height and width without restriction but the top rail must remain unaltered – vertical edges must be lipped in accordance with the instructions below (please refer to door edge lippings section). Single leaves up to 2260mm in height and up to 968mm in width may have the top rail removed but all edges must be lipped.

Glazing:

Up to 0.91 m² of glazing per leaf is approved in Sentry PRO LITE MDF (all configurations). Apertures must not be less than 100mm from any door edge. Multiple apertures are acceptable up to the maximum approved total area, with a minimum dimension of 80mm between apertures. The aperture shape is not restricted, providing the intumescent material and beads are proven to be compatible with that shape.

Approved glasses are:

6/7mm Pyroshield, 7mm Pyrobelite, 7.2mm Pyroguard, 7.5 Pyrodur Plus, 10mm Pyrodur, 12mm Pyrobel, 15mm Pyrostop. Alternative glass products may be used, providing relevant evidence generated in suitable timber door construction can be provided.

Approved proprietary glazing systems are:

Lorient System 36, Sealmaster Fireglaze 30, ISL Therm-A-Glaze 30, Mann McGowan Pyroglaze 30, Reddiplex R8193 glazing channel, Lorient Flexible Figure 1. Installation must be in accordance with the glass / glazing system manufacturer's recommendations.

Door frames:

Softwood or hardwood is approved in minimum density 510 kg/m³ in a minimum section of 70 x 32 mm after rebating / profiling. Single acting door frames must incorporate a 12 mm rebated or planted stop. Double acting frames must be scalloped or fitted with shoulders to maintain

specified gap dimensions. Frame joints must be morticed and tenoned, nailed or screwed and with no gaps. MDF doorframes are also approved. Please refer to the global assessment for details.

U Value:

The thermal performance of Sentry PRO LITE MDF evaluate with softwood door frame section 70 x 32, in flush door format, in accordance with B.S.EN ISO 10077-2: 2003, performed in an Approved Document L compliant configuration is:- 2.0W/m²K Report Reference Chiltern Dynamics Chilt/T04005 refers.

Intumescent materials:

ISL Therm-a-seal intumescent is approved in sections to correspond to required leaf sizes and configurations as shown in the table below. Note that intumescent seals may be fitted to the door edges or frames.

Door edge lippings:

6mm - 18mm square or 8 - 20mm rounded (maximum 2mm profiling) hardwood (minimum density 640 kg/m³) are required to vertical edges only. In areas of high humidity, all edges should be lipped. Glue lines should be UF, Cascamite or P.U. adhesives.

Overpanels:

Overpanels are permitted in all approved configurations providing they incorporate a transom of a minimum specification to that stated for door frames.

Installation Instructions

Guidance for various methods of sealing the frame to structural opening gap is given in BS 8214:2008, code of practice for Timber Fire Door Assemblies.

If you are required to cut down the overall size of the door, it is important that any reduction in leaf height is done from the bottom of the leaf so as to retain the top rail.

Lip all edges H/W using an appropriate glue line.

Three hinges should be fitted for all exterior doors, doors weighing over 20kg and interior doors where opposing sides are exposed to extreme variations in temperature and humidity, such as bathrooms and airing cupboards.

Glazed panels in doors must comply with the requirements observed for safety glass.

Glazing beads must be correctly fitted using approved compound or glazing tapes to both sides of the glass. Approved material must be used for fire doors.

Door Gaps: It is essential that door gaps between leaf edges and the door frame and between leaves at the meeting edge/overpanel junction in double leaves are a minimum of 2mm and a maximum of 4mm. Note: The leaf contains identical top and bottom rails so it is important to identify the top of the leaf prior to trimming the leaf height and lipping. NB: Ensure correct compliant Ironmongery and glazing systems when using in a fire door application.

PRO LITE MDF from Sentry	Latched Single Acting Doorsets	Unlatched & Double Acting Single Doorsets	Latched Single Acting Double Doorsets	Unlatched & Double Acting Double Doorsets
Leaf Sizes From: To:	2415 x 1513mm 3020 x 1210mm	2415 x 1488mm 2970 x 1210mm	2110 x 976mm 2406 x 915mm	2110 x 951mm 2356 x 915mm
Maximum Glazed Area:	Up to 0.91m ² per leaf for all configurations			
Frame Specification:	70 x 32mm Softwood/Hardwood - min density 510kg/m ³			
Approved Intumescent Materials Head/Jamb:	1 No. 15 x 4mm fitted centrally increase to 20 x 4mm for leaves over 2400mm high x 1200mm wide or if MDF frame used 25 x 4mm for leaves over 2800mm high	1 No. 15 x 4mm fitted centrally	1 No. 15 x 4mm fitted centrally increase to 20 x 4mm if MDF frame used Meeting Edges: 1 No. 15 x 4mm fitted centrally in one leaf only	
Supporting Technical Data:	Test reports RF04016, RF00158, RF015096 (AR2) covering Sentry MDF LITE Doors fire resistance tested to BS476 Part 22:1987 in various configurations and leaf sizes at the laboratories of Chiltern International Fire Ltd provide the basis for Assessment CHILTA04030 REVA. conducted to BS476:Part 22:1987			



CONTACT SENTRY PANEL PRODUCTS LTD

Head Office:
Sentry Panel Products Ltd
Muirhouses
Bo'ness
Edinburgh EH51 9SS

Regional Office:
Sentry Panel Products Ltd
Unit 10, M11 Business Link
Parsonage Lane,
Stansted CM24 8GF

Tel 00 44 (0) 1506 827538
Fax 00 44 (0) 1506 825996

Tel 00 44 (0) 1279 815285
Fax 00 44 (0) 1279 812975

Sentry product information is available on the worldwide web at www.sentrypanelproducts.com
email: info@sentrypanelproducts.com